

BATTERY DRILL

Description:

Combination drills for use where there are no power outputs, or leads are impractical. All battery powered drills are supplied with 240V mains chargers.

Key Specifications:

- 12v, 18v, 24v, 36v



	GSR 12 VE-2	GSR 14.4 VE-2	GSR 24 VE-2
Torque, max, hard screwing application	65 Nm	70 Nm	85 nm
Torque, max., soft screwing applications	26 Nm	30 Nm	44 Nm
No-load speed, 1st Gear:	0 / - 400 1/min	0 / - 400 1/min	0 / - 400 1/min
No-load speed, 2nd Gear	0 / - 1.400 1/min	0 / - 1.400 1/min	0 / - 1.300 1/min
Torque Setting Range (min/max)	2 / - 10Nm	2 / - 10Nm	2 / - 10Nm
Drill Spindle Thread	½"	½ Zoll	½ Zoll
Chuck Jaw Width	1,5 / 13 mm	1,5 / 13 mm	1,5 / 13 mm
Battery Voltage	12 V	14,4 V	24 V
Battery Capacity	2,4 Ah	2,4 Ah	2,6 Ah
Weight including battery, approx:	2,30 kg	2,40 kg	3,00 kg
Quick Change Chucks	13 mm	13 mm	
Charging Time	0,5 H	0,5 H	0,5 H
Torque Settings	15	15	15
Length	256,0 mm	256,0 mm	256 mm
Height	260 mm	260 mm	291 mm
Drilling Diameter - Wood	32,00 mm	32,00 mm	40,00 mm
Drilling Diameter - Steel	13,00 mm	13,00 mm	16,00 mm
Max. Screw Diameter	8 mm	10 mm	14 mm

BATTERY DRILL (continued)

Safety Information:



Operators Manual:

<http://www.fastline-group.com/files/pdf013-battery-drills.pdf>



Fastline Fred's Tips:

- Never force the drill bit through the rail.
- Always take a spare charged battery with you so you don't get caught short without power
- In case of breakdown call the Fastline Control Centre – 0845 450 2045

Fastline Limited

Marshgate Depot, Friarsgate, Greyfriars Road, Doncaster, DN1 1QW
T: +44 (0) 1302 303 555 F: +44 (0) 1302 303 564
E: info@fastline-group.com

